



油圧用ホース(アダプタ)

●アダプタタイプ:A




内径記号	ねじ R (PT) G (PT)	Y mm	L mm	A mm	B mm	概略 重量 g
04	1/4	19	37	13	16	40
06	3/8	22	41	15	18	60
08	1/2	27	48	18	20	100
12	3/4	36	54	20	22	170
16	1	41	58	22	23	240
20	1 1/4	50	66	25	27	420
24	1 1/2	55	69	25	29	480
32	2	70	76	29	30	720

●アダプタタイプ:B




内径記号	ねじ R (PT) G (PT)	Y mm	L mm	A mm	B mm	概略 重量 g
04	1/4	19	34	13	13	40
06	3/8	22	38	15	15	60
08	1/2	27	46	18	18	100
12	3/4	36	52	20	20	170
16	1	41	57	22	22	240
20	1 1/4	50	64	25	25	410
24	1 1/2	55	65	25	25	470
32	2	70	75	29	29	760

●アダプタタイプ:C




内径記号	ねじ R (PT) G (PT)	Y mm	L mm	A mm	B mm	概略 重量 g
04	1/4	19	34	13	13	40
06	3/8	22	38	15	15	60
08	1/2	27	46	18	18	100
12	3/4	36	52	20	20	170
16	1	41	57	22	22	240
20	1 1/4	50	64	25	25	410
24	1 1/2	55	65	25	25	470
32	2	70	75	29	29	760

●アダプタタイプ:D




内径記号	ねじ R (PT) G (PT)	Y mm	L mm	A mm	概略 重量 g
04	1/4	19	32	16	40
06	3/8	22	37	18	60
08	1/2	27	42	20	90
12	3/4	36	47	22	180
16	1	41	51	23	240
20	1 1/4	50	57	27	330
24	1 1/2	55	61	29	400
32	2	70	65	30	690

●アダプタタイプ:E




内径記号	ねじ R (PT) G (PT)	Y mm	L mm	A mm	最高使 用圧力 Mpa	概略 重量 g
04	1/4	19	40	13	34.5	60
06	3/8	22	42	15	34.5	80
08	1/2	27	49	18	34.5	130
12	3/4	36	57	20	27.5	250
16	1	41	63	22	20.5	330
20	1 1/4	50	71	25	17.0	500
24	1 1/2	55	74	25	10.5	580
32	2	70	79	29	10.5	970

●アダプタタイプ:F




内径記号	ねじ R (PT) G (PT)	Y mm	L mm	最高使 用圧力 Mpa	概略 重量 g
04	1/4	19	35	34.5	60
06	3/8	22	38	34.5	70
08	1/2	27	43	34.5	110
12	3/4	36	50	27.5	250
16	1	41	56	20.5	290
20	1 1/4	50	62	17.0	420
24	1 1/2	55	66	10.5	490
32	2	70	68	10.5	840

●アダプタタイプ:G




内径記号	ねじ R (PT) G (PT)	Y mm	L mm	A mm	概略 重量 g
04	1/4	19	29	13	40
06	3/8	22	34	15	50
08	1/2	27	40	18	100
12	3/4	36	45	20	180
16	1	41	50	22	230
20	1 1/4	50	55	25	350
24	1 1/2	55	57	25	410
32	2	70	64	29	680

●アダプタタイプ:H




内径記号	ねじ R (PT) G (PT)	X mm	C mm	E mm	A mm	B mm	概略 重量 g
04	1/4	17	25	24	11	16	50
06	3/8	19	30	28	13	18	100
08	1/2	24	36	32	15	20	160
12	3/4	30	43	37	17	22	250
16	1	36	50	41	19	23	410
20	1 1/4	46	57.5	49.5	22	27	730
24	1 1/2	50	63	54	22	29	920
32	2	65	73.5	61.5	26	30	1,810

●アダプタタイプ:I




内径記号	ねじ R (PT) G (PT)	X mm	C mm	E mm	A mm	B mm	概略 重量 g
04	1/4	17	25	21	11	13	60
06	3/8	19	30	25	13	15	90
08	1/2	24	36	30	15	18	150
12	3/4	30	43	35	17	20	260
16	1	36	50	40	19	22	390
20	1 1/4	46	57.5	47.5	22	25	740
24	1 1/2	50	63	50	22	25	900
32	2	65	73.5	60.5	26	29	1,580

●アダプタタイプ:J



内径記号	ねじ R (PT) G (PT)	X mm	C mm	E mm	A mm	B mm	概略 重量 g
04	1/4	17	21	23	11	16	50
06	3/8	19	23	25	13	18	80
08	1/2	24	28	28.5	15	20	120
12	3/4	30	31	32	17	22	190
16	1	36	35	35	19	23	300
20	1 1/4	46	41	42	22	27	530
24	1 1/2	50	42	45	22	29	590
32	2	65	50	50	26	30	1,090

●アダプタタイプ:K



内径記号	ねじ R (PT) G (PT)	X mm	C mm	E mm	A mm	B mm	概略 重量 g
04	1/4	17	21	20	11	13	40
06	3/8	19	23	22.5	13	15	70
08	1/2	24	28	27	15	18	120
12	3/4	30	31	30.5	17	20	200
16	1	36	35	34	19	22	300
20	1 1/4	46	41	44	22	25	570
24	1 1/2	50	42	44	22	25	650
32	2	65	50	51	26	29	1,200